


# DIRECTIONAL LIGHT

## RXD-01-BAR



### SPECIFICATIONS

**CONSTRUCTION:** Cast brass bullet, adjustable cast brass swivel with 240° rotation  
**LENS:** High impact clear tempered convex glass  
**LAMP SUPPLIED:** 20 watt MR16 FL (BAB) 5000 hours average rating (50 w. max)  
**LAMP OPTIONS:** MR16 Ultra, 10,000 hours, MR16 Titan, 18,000 hours, or ARROW LED MR16, 50,000 hrs. Consult factory for wattage and beam spread  
**SOCKET:** High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires  
**WIRING:** Black 3 foot 18/2 SPT-1W from base of fixture (12v. only)  
**CONNECTION:** We recommend FA-05 Quick Connector (not supplied) from fixture to main cable (1/2", 10/2 or 8/2 only) 12v. only  
**MOUNTING:** Black 8.5" ABS stake threaded 1/2" NPS  
**FINISH:** Brass acid rust (-BAR)



LAMP AND STAKE  
**INSTALLED TO SAVE YOU  
 TIME AND MONEY**



### ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	MAX. WATTAGE	SUPPLIED MOUNT	EST. SHIP. WEIGHT
RXD-01-BAR	20w MR16 Cast Brass Bullet Acid Rust Finish	50w.	Black ABS Stake	3 lbs.

### MOUNTING ACCESSORIES


15" 381mm  
 1.63" 41mm  
 20" 508mm  
 3" 76mm  
 3" 76mm  
 20" 508mm  
 3" 76mm  
 5.5" 140mm  
 1.5" 38mm  
 3" 76mm  
 10" 254mm  
 15" 381mm  
 21" 533mm  
 31" 787mm  
 41" 1041mm  
**FA-24-Strap-10"-41"**  
 3" 76mm  
 4" 102mm  
 8" 203mm  
 26" 660mm  
**FA-30-4**  
**FA-30-8**  
 0.9" 23mm  
**FA-111-TREE-BRS (10"-41")**  
**FA-24-BRS**  
 0.9" 23mm  
 4.5" 114mm  
 4.5" 114mm  
**FA-24-LG-SPUN-BRS**  
**FA-24-LG-DH-SPUN-BRS**  
**FA-24-LG-CST-BRS**  
**FA-24-LG-DH-CST-BRS**  
 10" 254mm  
 13" 330mm  
 15" 381mm  
 21" 533mm  
**FA-30** **FA-31** **FA-32** **FA-33** **FA-34**  
**-BRS = Brass Models (Arrow: couplers)**  
**BRASS STEM EXTENSIONS**  
 with 1/2" NPS female couplers

### COLOR / BEAM/GLARE CONTROL ACCESSORIES

2" 51mm  
**FA-08-21**  
 2" 51mm  
**FA-11-BLUE/-GREEN**  
**-AMBER/-RED**  
 2.25" 57mm  
**FA-104-SB**  
 2.00" 51mm  
**FA-99**  
 2.25" 57mm  
**FA-98**

**FA-08-21** Round 1/8" Hex Cell Louver  
**FA-11-BLUE** Blue Tempered Flat Glass Lens  
**FA-11-GREEN** Green Tempered Flat Glass Lens  
**FA-11-AMBER** Amber Tempered Flat Glass Lens  
**FA-11-RED** Red Tempered Flat Glass Lens  
**FA-99** Clear Tempered Convex Glass Lens  
**FA-98** Linear Spread Tempered Glass Lens  
**FA-104-SB** Wide Spread Sand Blasted Glass Lens Softener

### LIGHT DISTRIBUTION AND PHOTOMETRICS



### JOB INFORMATION

Type: \_\_\_\_\_ Date: \_\_\_\_\_  
 Job Name: \_\_\_\_\_  
 Cat. No.: \_\_\_\_\_  
 Lamp(s): \_\_\_\_\_  
 Specifier: \_\_\_\_\_  
 Contractor: \_\_\_\_\_  
 Notes: \_\_\_\_\_

12v. fixtures: 25 foot 16/2 fixture lead wire available; add -25F to catalog number.  
 For use with Focus CPC or hub supplied by others.

**FOCUS INDUSTRIES INC.**  
 25301 COMMERCENTRE DRIVE  
 LAKE FOREST, CA 92630  
 www.focusindustries.com  
 sales@focusindustries.com  
 (949) 830-1350 • FAX (949) 830-3390



landscape • entertainment • architectural • hospitality • illumination

# NEW PRODUCT eNEWS

[www.focusindustries.com](http://www.focusindustries.com)

## RXD-01-BAR



- Introducing a NEW product from FOCUS
- Same great FOCUS quality with a reduced price
- Cast brass bullet with adjustable cast brass swivel
- Clear Tempered Convex glass lens
- 20watt MR16 FL (BAB) Lamp supplied
- Black ABS mounting stake supplied
- 10k ULTRA, 18k TITAN MR16 or 50K 4w ARROW LED MR16 optional

